



Vertical cassette blind

markilux 620 tracfix

Slender and stable in wind with tracfix cover guidance system.

Product properties

Wind resistance class 3

Beaufort 6 → 38–48 km/h → 10.5–13.4 m/s → 24–30 mph

side view




unit when closed




reveal fixture




front profile finishes flush with the end of the guide rails




with tracfix system, the continuous lateral cover guidance system that leaves no gap between the cover and guide rails




cover guidance system in the tracfix profile



section of guide rail with tracfix profile



Optional radio-controlled motor RTS sundrive with solar module (433 MHz) ¹⁾



1) optional configuration

Product properties

Description

- slender, compact vertical cassette blind with angled guide rails and gravity-fed cover tensioning system – for areas up to 12 m².

Special features

- fully encompassing cassette that protects the cover perfectly
- attractive appearance without visible screws
- supplied as standard with a hard-wired motor
- with tracfix system, the continuous lateral cover guidance system that leaves no gap between the cover and guide rails – gives improved wind stability and a cleaner appearance
- good blind closure guaranteed by virtue of the small protuberances on the bottom profile end caps that close firmly against the cassette
- fixture directly through the angled rails – the cassette is positioned right against the wall

Dimensions

- single unit: 61 cm – 400 cm in width, maximum height 400 cm (depending on the width)
- maximum width × height: 300 cm × 400 cm / 400 cm × 300 cm
- intermediate sizes are available

Roller tube and lateral bearings

- round roller tube Ø 63 mm with keyway, galvanised steel
- the roller tube bearing is made of stainless steel

Blind profiles

- extruded aluminium, in façade quality, powder coated
- cassette profile in one piece, oblong, height × depth 110 mm × 95 mm
- angled guide rails in two pieces, width × depth 27 mm × 48 mm
- bottom profile angular, height × depth 32 mm × 40 mm

Side caps

- the cassette end caps are made of die-cast aluminium, powder coated
- the bottom profile end caps are made of high-quality plastic, powder coated

Fixture brackets

- self-supporting cassette attached to the top of the angled guide rails
- without brackets, fixture directly through the angled guide rails, face or reveal fixture

Frame colours

markilux blind colours without surcharge

traffic white RAL 9016

metallic aluminium RAL 9006

grey brown, similar to RAL 8019



off-white textured finish, 5233 ¹⁾

stone grey metallic, 5215 ¹⁾

anthracite metallic, 5204 ¹⁾



Havana brown textured finish, 5229 ¹⁾



Non-standard powder-coated finish

Bespoke frame colours at a surcharge – matt, metallic and pearl finishes as well as other colour ranges (DB, Tiger etc.) on request. All frame colours are available at a surcharge with enhanced corrosion protection.

¹⁾ textured finish

Colours may differ slightly from those depicted in both hue and finish.

Dimensions and configuration options

Single unit

		Overall blind width						Minimum blind width	
		100	150	200	250	300	350	400	
Order dimensions		61 ²⁾ 100	101 ³⁾ 150	151 200	201 250	251 300	301 350	351 400	Hard-wired motor Radio-controlled motor
AH	1201 ¹⁾								64 77 ²⁾³⁾
	160								
	200								
	250								
	300								
	350						—	—	
	400						—	—	

dimensions in cm

1) = minimum unit height 65 cm

2) = minimum width 60 cm in the case of a motor with sundrive and E-box

3) = minimum width 138 cm in the case of motor with sundrive without E-box

 = optional with sundrive motor and E-box

 = optional with sundrive motor without E-box

AH = unit height

Operation

standard optional

crank handle	—	—
crank handle, operation from the rear	—	—
crank handle, operation from inside the building	—	—
hard-wired motor	✓	—
radio-controlled motor io, 868 MHz	—	✓
radio-controlled motor RTS, 433 MHz	—	✓

Coupled Blind

not available

Optional accessories

automatic controls (light, wind, rain)
--

N.B! Important background information can be found in the chapter "Optional Accessories".

Blind cover

fabric range no.

standard

optional

sunvas	301.. / 309..-315..	✓	—
sunsilk	324.. / 325.. / 328.. / 369..	✓	—
perfortex	331.. / 332..	✓	—
sunvas (250 cm)	31008, -09, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17	✓	—
transolair	338..	—	✓
transolair (120 cm)	339..	—	✓
sunvas (320 cm)	31008, -09	✓	—
vuscreen Alu	317..	—	✓
Fibreglass Screen Fabrics	272..	—	✓
Soltis Perform 92	92-20..	—	✓
perla	370..	—	—
perla FR	374.. / 375..	—	—

Awning fabrics

Fabric pattern series | Their applications and manufacture

sunvas / transolair 120 cm

Fabric width 120 cm

Fabric pattern no. 301.. / 309.. – 315.. / 339..

		Overall awning width					
		150	200	250	300	350	400
AH	150						
	200						
	250						
	300						
	350						
	400						

sunsilk

Fabric width 120 cm

Fabric pattern no. 324.. / 325.. / 328.. / 369..

		Overall awning width					
		150	200	250	300	350	400
AH	150						
	200						
	250						
	300						
	350						
	400						

sunvas

Fabric width 250 cm

Fabric pattern no. 310081⁰⁹¹⁾, -13¹⁶⁾, -18, -25, -27, -28, -31, -36, -37, -57, -58, -31109, -14 / 17, -, -

		Overall awning width					
		150	200	250	300	350	400
AH	150						
	200						
	240						
	300				1)		
	350				1)		
	400				1)		

1) also available in fabric width 320 cm – then seamless

transolair

Fabric width 250 cm

Fabric pattern no. 338..

		Overall awning width					
		150	200	250	300	350	400
AH	150						
	200						
	240						
	300						
	350						
	400						

dimensions in cm

N.B!: Width of the outer panels in covers with vertical joints max. 35 cm

☐ = vertical panel joints (panel width approx. 120 cm)

■ = seamless

■ = horizontal panel joint(s)

☐ = not available

AH = unit height

Awning fabrics

Fabric pattern series | Their applications and manufacture

perfortex

Fabric width 120 cm

Fabric pattern no. 331.. / 332..

		Overall awning width					
		150	200	250	300	350	400
AH	150						
	200						
	250						
	300						
	350						
	400						

vuscreen Alu

Fabric width 252 cm

Fabric pattern no. 317..

		Overall awning width					
		150	200	250	300	350	400
AH	150						
	200						
	250						
	300						
	350						
	400						

glass fibre screen

Fabric width 250 cm

Fabric pattern no. 272..

		Overall awning width					
		150	200	250	300	350	400
AH	150						
	200						
	240						
	300						
	350						
	400						

Soltis Perform 92

Fabric width 177 cm

Fabric pattern no. 277..

		Overall awning width					
		150	177	250	300	350	400
AH	150						
	170						
	250						
	300						
	350						
	400						

dimensions in cm

N.B!: Width of the outer panels in covers with vertical joints max. 35 cm

= vertical panel joints (panel width approx. 120 cm)

= seamless


= horizontal panel joint(s)

= not available


AH = unit height

Dimension overview


Single unit



Two single units




- * = extension when retracted
- AH = order measurement = unit height
- BA = width between fixture points (fixture type 8)
- EA = single unit
- LF = length of the guide rail
- M = order dimension = blind width
- (M) = motor
- SF = visible cover area



dimensions in mm

Dimension overview fixture combination 8

Face fixture



- *

= extension when retracted
- AH

= order measurement = unit height
- ABO

= number of drill holes in the range xxx
- BA

= width between fixture points
- LF


= length of the guide rail
- M

= order dimension = blind width
- SF

= visible cover area
- dimensions in mm

Dimension overview fixture combination 9

Reveal fixture



- * = unit height when retracted

AH = order measurement = unit height = IW - 10 mm

AU = exterior

ABO = number of drill holes in the area xxx

IN = interior


IW = height of opening
- LF** = length of the guide rail

M = order dimension = blind width


NB = reveal width

SF = visible cover area
- dimensions in mm

Reveal fixture in a top window well



Motor cable exit point



* = extension when retracted

 = standard


 = options

 = optionally (surcharge)

dimensions in mm

sundrive dimension overview

Solar module in the cassette



The sundrive solar module is either


- integrated on the bearing side in the cassette (for awning size width 138–250 cm × maximum height 300 cm) or
- connected on the motor side in the external E-box housing (for awning size width 60–250 cm × maximum height 300 cm) in order to be able to make use of an optimal incidence of sunlight with flexible installation or so that awnings which are not so wide can be powered using solar energy.

You can choose which side the motor is fitted; this, however, also determines the position of the solar panel and / or the E-box.


The solar panel (without E-box) is always on the bearing side and the E-box is always installed on the same side as the motor.

Dimension overview for sundrive with E-box

Solar module in the E-box



Motor cable exit point for sundrive with E-box



- 01
- 02
- 03
- 04
- 05
- 06
- 07**
- 08
- 09
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20